

STANDARD FEMALE DIES

<p>20.08</p> <p>12</p>	<p>20.09</p> <p>40</p> <p>V 16-22=88° V 35-50=85°</p>	<p>20.11/32/40/50</p> <p>35 36 37</p> <p>V = 85° V = 32-40-50</p>	<p>20.11/63</p> <p>38</p> <p>V = 85°</p>
<p>20.11/80</p> <p>13</p> <p>V = 85°</p>	<p>20.11/100</p> <p>18</p> <p>V = 85°</p>	<p>20.11/125</p> <p>39</p> <p>V = 85°</p>	<p>20.11/160</p> <p>14</p> <p>V = 85°</p>
<p>20.12/90°</p> <p>23</p> <p>V = 90°</p>	<p>20.13/90°</p> <p>24</p> <p>V = 90°</p>	<p>20.14/88°</p> <p>26</p> <p>V = 88°</p>	<p>20.15/88°</p> <p>27</p> <p>V = 88°</p>
<p>20.12/35°</p> <p>V = 35°</p>	<p>20.12/35°</p> <p>V = 35°</p>	<p>20.12/35°</p> <p>22</p> <p>V = 35°</p>	<p>20.12/35°</p> <p>25</p> <p>V = 35°</p>

Our standard bending dies are always available in our stock in lengths of mms.: 415, 835 and sectioned. Each bending die is checked very carefully in order to guarantee its **QUALITY, PRECISION AND**